

Product Name: ThermOweld® Weld Metal  
Revision Date: 14 July 2015



## SAFETY DATA SHEET

### SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT:**

**Product Identifier:** ThermOweld® Weld Metal

**Product Description:** Gray / silver granular metal

**Recommended Use:** Exothermic welding metal

**COMPANY IDENTIFICATION:**

**Supplier:** Continental Industries, a Division of Burndy LLC.  
1140 North 129<sup>th</sup> East Ave  
Tulsa, OK 74116 USA  
(918) 627-5210

**24 Hour Emergency (INFOTRAC)** (800) 535-5053  
(352) 323-3500 (*International*)

**TELEPHONE NUMBER FOR INFORMATION:** (800) 558-1373

### SECTION 2 HAZARDS IDENTIFICATION

**CLASSIFICATION:**

Health	Environmental	Physical
<ul style="list-style-type: none"><li>Acute Toxicity - Oral, Category 4</li><li>Skin Irritation - Category 3</li><li>Eye Irritation - Category 2B</li><li>Specific Organ Toxicity – Single Exposure - Category 3</li></ul>	<ul style="list-style-type: none"><li>Acute toxicity - Category 1</li></ul>	

**LABELING:**

**Symbols:**



Warning



Environmental Hazard

**Signal Word:** Warning

**Hazard Statements**

- H 302: Harmful if swallowed
- H 411: Toxic to aquatic life and may cause long lasting harmful effects
- H 320: Causes eye irritation
- H 316: Causes mild skin irritation
- H 335: May cause respiratory irritation

**Precautionary Statements**

- P 261: Avoid breathing dust/fume/gas/mist/vapors/spray
- P 264: Wash hands thoroughly after handling
- P 280: Wear protective gloves/clothing
- P 270: Do not eat, drink or smoke when using this product
- P 271: Use only outdoors or in a well-ventilated area

Precautionary Statements	Precautionary Statements
<ul style="list-style-type: none"> <li>• P301 + P312: If swallowed: Call a POISON CENTER/doctor/etc if you feel unwell</li> <li>• P304 + P340: If inhaled: Remove person to fresh air and keep comfortable for breathing</li> <li>• P332 + 313: If skin irritation occurs: Get medical advice/attention</li> <li>• P330 Rinse Mouth</li> <li>• P305 + P351 + P338: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present. Continue rinsing</li> </ul>	<ul style="list-style-type: none"> <li>• P337 + P313: If eye irritation persists: Get medical advice/attention.</li> <li>• P403 + P233: Store in a well-ventilated place. Keep container tightly closed.</li> <li>• P405: Store locked up</li> <li>• P391: Collect spillage</li> <li>• P501: Dispose of contents in accordance with local/regional regulations. Container doesn't require special disposal.</li> <li>• P 273: Avoid release to the environment</li> </ul>

**SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS**

**Reportable Hazardous Substance(s) or Complex Substance(s):**

Name	Common Name/Synonym	CAS #	Percentage	Impurities
Cuprous Oxide	Copper Oxide, $Cu_2O$ , Cuprite	1317-39-1	70-90	<10% Cupric Oxide <1% Copper
Aluminum Copper Alloy 50 Copper 50 Aluminum	-	7440-50-8 7429-90-5	15-25	None Known
Flourspar	-	Mixture	0-5	None Known
Tin	-	7440-31-5	0-5	None Known
Calcium Silicon	-	Mixture	0-5	None Known
Lithium Fluoride	-	7789-24-4	0-5	None Known

\* All concentrations are percent by weight unless material is a gas. Gas concentrations are in percent by volume.  
 The exposure limits of this product, when allowed to enter the environment as dust particulate, are covered under the rules of 29 CFR 1910.1000, Table Z -3, "All inert or nuisance dusts, whether mineral, inorganic or organic."

**SECTION 4 FIRST AID MEASURES**

**ROUTES OF ENTRY:** Ingestion, Contact

**EMERGENCY AND FIRST AID PROCEDURES:**

Inhalation: Breathing airborne particles or dust may cause irritation to respiratory tract. Remove affected person to fresh air; if symptoms persist seek medical attention.

Eye Contact: Direct contact can cause eye irritation. Remove contact lenses. Flush eyes with clear running water for 15 minutes while holding eyelids open; if irritation persists, seek medical attention.

Skin Contact: Prolonged contact may lead to contact dermatitis. Remove contaminated clothing; wash affected area with soap and water; launder contaminated clothing before reuse; if irritation persists, seek medical attention.

Ingestion: May cause gastric distress, stomach pains, vomiting and diarrhea. Give two glasses of water for dilution; induce vomiting as directed by medical personnel; never give anything by mouth to an unconscious person; seek medical attention.

**SECTION 5 FIRE FIGHTING MEASURES**

**GENERAL HAZARDS:**

The materials are not explosive; ignition temperatures are in excess of 850° F (454C) for starting material and 1750° F (954C) for base material. They are not shock sensitive, nor are they subject to spontaneous ignition. Should the material be accidentally ignited, the immediate and direct application of large volumes of water will effectively retard the spread of fire and control it. Large amounts of dense, dusty smoke will be liberated during an accidental fire. Smoke, oxides of carbon; fumes of copper and aluminum, small amounts of fluoride fume or hydrofluoric acid fume may be released under ignition.

**EXTINGUISHING MEDIA**

**Appropriate Extinguishing Media:** Use carbon dioxide, water, water fog, dry chemical, chemical foam, dry sand.

**Inappropriate Extinguishing Media:** None known

**FIRE FIGHTING PROCEDURES**

**Fire Fighting Instructions:** Firefighters must wear full face piece self - contained breathing apparatus in positive pressure mode. Water may be used from a distance once reaction is complete. Molten metal contact with water can produce pockets of superheated steam.

**Unusual Fire Hazards / Combustion Products:** ThermOweld® copper base welding/joining materials are exothermic mixtures, which when reacted, produces a thermite reaction and hot molten materials with temperatures in excess of 4000° F (2204C) and a localized release of smoke.

**SECTION 6 ACCIDENTAL RELEASE MEASURES**

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:**

Confine and segregate product for reuse; place material into approved containers for disposal; for spills in excess of allowable limits (RQ) notify the National Response Center (800) 424 - 8802; refer to CERCLA 40 CFR 302 for detailed instructions; refer to SARA Title III, Section 313, 40 CFR 372 for reporting requirements. Do not discharge into lakes, ponds, streams or public waters.

**ENVIRONMENTAL PRECAUTIONS:**

Copper and Aluminum can be serious marine pollutants. Prevent entry into waterways, sewer, basements or confined areas. In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. The National Response Center can be reached at (800) 424-8802; refer to CERCLA 40 CFR 302 for detailed instructions; refer to SARA Title III, Section 313, 40 CFR 372 for reporting requirements.

**CLEAN UP AND CONTAINMENT METHODS:**

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do it without putting yourself in harm's way. All equipment used when handling the product must be grounded. Avoid breathing vapors/fumes/dusts and wear specific protective equipment specified in section 8. Use clean non-sparking tools to collect material and segregate material for reuse. If material cannot be reused place material in appropriate disposal container.

Spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

**SECTION 7 HANDLING AND STORAGE**

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:**

Before using ThermOweld® Exothermic Process, personnel should be trained by a ThermOweld® representative. Read and understand the instruction sheet packaged with the mold, and observe all general and safety instructions. ThermOweld® products are to be used i

Storage of ThermOweld® exothermic materials should be in a clean dry area and restricted to access by authorized personnel only. Do not subject to rough handling or physical damage, nor excessive vibration. Store in accordance with "This Side Up" labels. Protect from weather and moisture. DO NOT USE PRODUCTS THAT HAVE BEEN EXPOSED TO MOISTURE. Keep away from children. Do not tamper with valve. Keep away from ignition sources prior to use. Do not spray in eye, inhale vapors, or ingest. Use product in only well ventilated areas. Improper use can lead to exposure of molten metal and reaction by-products.

Product Name: ThermOweld® Weld Metal  
Revision Date: 14 July 2015



**SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION**

**EXPOSURE LIMIT VALUES:**

Component Name	CAS #	OSHA PEL	NIOSH REL	ACGIH TLV
Cuprous Oxide	7440-50-8	0.1 mg/m <sup>3</sup> TWA (Fume) 1 mg/m <sup>3</sup> TWA (Dust)	0.1 mg/m <sup>3</sup> TWA (Fume) 1 mg/m <sup>3</sup> TWA (Dust)	0.2 mg/m <sup>3</sup> TWA (Fume) 1 mg/m <sup>3</sup> TWA (Dust)
Cupric Oxide	1317-38-0	5 mg/m <sup>3</sup> TWA (Fume) 15 mg/m <sup>3</sup> TWA (Total Dust)	5 mg/m <sup>3</sup> TWA (Fume) 10 mg/m <sup>3</sup> TWA (Total Dust)	Not Established
Aluminum	7429-90-5	15 mg/m <sup>3</sup> TWA (Total Dust)	10 mg/m <sup>3</sup> TWA (Total Dust) 5 mg/m <sup>3</sup> TWA (Welding Fumes)	10 mg/m <sup>3</sup> TWA
Calcium Fluoride	7789-75-5	Not Established	Not Established	Not Established
Tin	7440-31-5	2 mg/m <sup>3</sup> TWA	2 mg/m <sup>3</sup> TWA	2 mg/m <sup>3</sup> TWA
Calcium Silicon	Mixture	Not Established	Not Established	Not Established
Lithium Fluoride	7789-24-4	Not Established	Not Established	Not Established
Flouride as F	-	2.5 mg/m <sup>3</sup> TWA	2.5 mg/m <sup>3</sup> TWA	2.5 mg/m <sup>3</sup> TWA

**PERSONAL PROTECTIVE EQUIPMENT:**

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

**Respiratory Protection:** NIOSH approved respirator designed to remove airborne particulate present in excess of maximum allowable concentrations due to secondary operations such as mixing, spraying, sanding, buffing, etc. Refer to 29 CFR 1910.134 or European Standard EN 149 for regulations.

**Hand protection:** Neoprene or rubber gloves may be used when handling this product.

**Eye protection:** Protective eyeglasses or chemical safety goggles. Refer to 29 CFR 1910.133 or European Standard EN166.

**Skin and Body Protection:** No special protection is ordinarily required under normal conditions of use for skin and body. Wear appropriate clothing to the application used, along with all other personal protective equipment.

**Other Protective Clothing or Equipment:** Safety eyebath nearby

**Specific Hygiene Measures:** Practice safe workplace habits. Minimize body contact with this, as well as all chemicals in general.

**SECTION 9 PHYSICAL/CHEMICAL PROPERTIES**

Typical physical and chemical properties are given below. Consult the Supplier in Section 1 for additional data.

**GENERAL INFORMATION:**

**Physical State:** Solid/  
**Color:** Gray/ Silver  
**Odor:** Characteristic odor  
**Odor Threshold:** Not Available

**IMPORTANT HEALTH, SAFETY, AND ENVIRONMENTAL INFORMATION:**

**Appearance:** Gray/ Silver granules  
**pH:** Not Applicable  
**Viscosity:** Not Applicable  
**Freezing Point:** Not Available

Product Name: ThermOweld® Weld Metal  
 Revision Date: 14 July 2015

**Boiling Point:** Not Applicable  
**Flash Point:** Not Applicable  
**Evaporation Rate:** Not Applicable  
**Lower Flammability Limit:** Not Applicable  
**Upper Flammability Limit:** Not Applicable  
**Vapor Pressure:** Not Applicable  
**Vapor Density (Air=1):** Not Applicable  
**Specific Gravity (Water = 1):** Approximately 6.0  
**Solubility in Water:** Insoluble  
**Coefficient of Water/Oil Distribution:** Not Available  
**Auto-ignition Temperature:** > 1750 °F (> 955 °C)  
**Percent Volatile, wt. %:** Not Available  
**VOC content, wt. %:** Not Available

<b>SECTION 10</b>	<b>STABILITY AND REACTIVITY</b>
-------------------	---------------------------------

**STABILITY:** Stable under normal storage conditions.

**CONDITIONS TO AVOID:** Avoid generating airborne dust, avoid moisture

**INCOMPATIBLE MATERIALS:** Strong oxidizers, strong acids

**HAZARDOUS DECOMPOSITION PRODUCTS:** Decomposition will not occur if handled and stored properly. In case of fire, smoke, oxides of carbon, fumes of copper and aluminum, and small amounts of fluoride fume or hydrofluoric acid fume may be released under ignition.

**POSSIBILITY OF HAZARDOUS REACTIONS:** HAZARDOUS POLYMERIZATION will not occur.

<b>SECTION 11</b>	<b>TOXICOLOGICAL INFORMATION</b>
-------------------	----------------------------------

Ingredient	LD50 of ingredient (Specify species and Route)	Sources
Cuprous Oxide	LD <sub>50</sub> : 470 mg / kg Oral-Rat LC <sub>50</sub> : 5 mg / m <sup>3</sup> / 24H Inhalation - Rat	RTECS, EPA HSNO CCID
Cupric Oxide	LD <sub>50</sub> : 470 mg / kg Oral-Rat LC <sub>50</sub> : Not Established	RTECS
Aluminum (Fume or Dust)	LC <sub>50</sub> : Not Established LD <sub>50</sub> : Not Established	-
Calcium Fluoride	LD <sub>50</sub> : Not Established LC <sub>50</sub> : Not established	-
Tin	LD <sub>50</sub> : Not Established LC <sub>50</sub> : Not established	Insufficient data
Iron Oxide, Black	LD <sub>50</sub> : Not established LC <sub>50</sub> : Not established	Insufficient data
Calcium Silicon	LD <sub>50</sub> : Not established LC <sub>50</sub> : Not established	Insufficient data
Lithium Fluoride	LD <sub>50</sub> : 608 mg/kg Oral - Rat LC <sub>50</sub> : Not established	RTECS

**ACUTE EFFECTS:**

**Eye Contact:** Direct contact with eyes may cause irritation.

**Skin Contact:** None expected, however, prolonged contact may cause irritation.

**Inhalation:** Breathing airborne particles or dust from mixing, spraying, sanding, grinding, etc. may cause irritation to respiratory tract. Contains substances which are considered nuisance dusts that require a NIOSH approved respirator when airborne particulate exceeds maximum allowable limit.

**Additional Target Organ Effects:** Renal and hepatic toxicity.

Product Name: ThermOweld® Weld Metal  
 Revision Date: 14 July 2015

**Ingestion:** May cause gastric distress, stomach pains, vomiting and diarrhea

**Carcinogenicity:** IARC: NO ACGIH: NO NTP: NO OSHA Regulated: NO

**CHRONIC/OTHER EFFECTS:**

Product is an eye, skin and respiratory irritant. Products containing tin can cause allergic contact dermatitis. Acute copper poisoning after ingestion can cause liver injury, methemoglobinemia and hemolytic anemia. Acute renal failure may result, secondary to massive hemoglobinuria. Iron Oxide fumes can cause metal fume fever and prolonged inhalation can cause damage to the liver and kidneys.

**SECTION 12 ECOLOGICAL INFORMATION**

**ECOTOXICITY:**

Ingredient	LC <sub>50</sub> and Species	Conclusion
Cuprous Oxide	75 µg/L/96 hr Zebra Danio Fish 173 µg/L/96 hr Sheepshead Minnow	
Aluminum Copper Alloy	Not Available	-
Tin	Not Available	Insufficient Data
Calcium Silicon	Not Available	Insufficient Data
Calcium Fluoride	Not Available	Insufficient Data
Lithium Fluoride	Not Available	-

**Environmental Fate:**

There is limited data regarding the mobility, degradability and potential for bioconcentration in aquatic species for the ingredients of this product. Evidence suggests that copper does not have significant mobility in soil unless under acidic conditions. Copper and copper oxides can be highly toxic to aquatic species. Aluminum contamination can be toxic to aquatic species. Industrial products should not be discharged to sewers or other water sources to prevent the risks of long term adverse effects and environmental contamination.

**SECTION 13 DISPOSAL CONSIDERATIONS**

**WASTE DISPOSAL METHOD:**

Avoid discharge into natural waters. Ultimate disposal of the chemical must consider: the material's impact on air quality; potential migration in soil or water; effects on animal, aquatic and plant life; and conformance with environmental and public health regulations.

According to the European Waste Catalogue, waste codes are application specific and should be assigned by the user based on the application for which the product is used. Dispose of in accordance with Local, State, and Federal Regulations. Do not flush to sanitary sewer or waterway. Refer to "40 CFR Protection of Environment Parts 260 - 299" for complete waste disposal regulations. US EPA guidelines for the classification determination are listed in 40 CFR parts 261.3. Consult your local, state, or Federal Environmental Protection Agency before disposing of any chemicals to ensure complete and accurate classification.

**SECTION 14 TRANSPORTATION**

**General Information:**

Due to the limited quantities of hazardous material per package all ThermOweld® powders are shipped in non-bulk packaging under provisions outlined in 49 CFR 171.4 "Marine Pollutants" and the exception 49 CFR 171.4(c)(2)

Guidance to Transport in Bulk: Classify by UN3077 and use standard packing practices as outlined in the US Code of Federal Regulations.

- UN Number: UN3077
- UN Proper Shipping Name: Environmentally Hazardous Substance, solid n.o.s.
- Transport Hazard Class: Class 9
- Packing Group Number: Group III
- Environmental Hazards: Severe Marine Pollutant

Product Name: ThermOweld® Weld Metal  
Revision Date: 14 July 2015

**thermOweld®**

**SECTION 15**

**REGULATORY INFORMATION**

**TSCA (USA - Toxic Substance Control Act):** All components of this product are listed on the U.S. Toxic Substances Control Act Chemical Inventory (TSCA Inventory) or are exempted from listing because a Low Volume Exemption has been granted in accordance with 40 CFR 723.50.

**EPCRA:** This material contains no extremely hazardous substances.

**SARA (311/312) REPORTABLE HAZARD CATEGORIES:** Yes – Immediate Health

**SARA (313) TOXIC RELEASE INVENTORY:** 7429-90-5 Aluminum (Fume or Dust)  
N100 Copper Compounds

**CERCLA (USA - Comprehensive Response Compensation and Liability Act):** The Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) has notification requirements for releases or spills to the environment (ingredient: copper) of the Reportable Quantity (RQ for this mixture > 24000 lbs) or greater amounts, if < 4µ diameter, according to 40 CFR 302.

**California Prop 65, Safe Drinking Water and Toxic Enforcement Act of 1986:** There are no chemicals present known to the state of California to cause cancer or reproductive toxicity.

**CPR (Canadian Controlled Products Regulations):** This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.  
WHMIS Classification: Not controlled

**IDL (Canadian Ingredient Disclosure List):** Components of this product identified by CAS number and listed on the Canadian Ingredient Disclosure List are shown in Section 2.

**DSL / NDSL (Canadian Domestic Substances List / Non-Domestic Substances List):** Components of this product identified by CAS number are listed on the DSL or NDSL, or are otherwise in compliance with the New Substances Notification (NSN) regulations. Only ingredients classified as "hazardous" are listed in Section 2 unless otherwise indicated.

**EINECS (European Inventory of Existing Commercial Chemical Substances):** Components of this product identified by CAS numbers are on the European Inventory of Existing Commercial Chemical Substances.

WGK Water Quality Rating: 1      VbK Index:

**EU RISK (R) AND SAFETY (S) PHRASES:**

R11: Highly flammable

R 15: Contact with water liberates extremely flammable gases

R 17: Spontaneously flammable in air

R 20/22: Harmful by inhalation and if swallowed

R 36/37/38: Irritating to the eyes, respiratory system and skin

S 22: Do not breathe the dust.

S36/37/39: Wear suitable protective clothing, gloves and eye/face protection



Product Name: ThermOweld® Weld Metal  
Revision Date: 14 July 2015



<b>SECTION 16</b>	<b>OTHER INFORMATION</b>
-------------------	--------------------------

**HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMIS) RATINGS:**

Health - 1      Flammability - 0      Physical Hazard - 0      PPE – E

**THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:**

<b>Revision Date</b>	<b>Description</b>	<b>Sections Affected</b>
6/19/14	SDS update	All
7/22/14	Spelling and grammar check	All
12/19/14	Pictogram update	2
1/7/2015	Formatting and transportation regulations	All/14
7/14/15	General Review	All

----- This SDS provides a good faith representation of information believed to be accurate as of the last revision date. This document does not create any express or implied product warranties. Since conditions of use are beyond the control of Burndy LLC, all risks associated with product use are assumed by the user. -----